

Categories		2-way Loudspeaker					
Model Name		CHR15	CHR12M	CHR10	CHR15	CHR12M	CHR10
DME library file name		CHR15.cel	CHR12M.cel	CHR10.cel	CHR15_foh.cel	CHR12M_moni.cel	CHR10_foh.cel
Drive Mode		Passive	Passive	Passive	Passive	Passive	Passive
Output Name		Full-range	Full-range	Full-range	Full-range	Full-range	Full-range
Gain	(dB)	0.0	0.0	0.0	0.0	0.0	0.0
Delay	(ms)	none	none	none	none	none	none
Polarity		Normal	Normal	Normal	Normal	Normal	Normal
HPF	Freq (Hz)	37.5	45.0	45.0	36.5	54.6	45.0
	Slope (dB)	24	24	24	24	24	24
	Type	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth
LPF	Freq (Hz)						
	Slope (dB)						
	Type						
PEQ1	Freq (Hz)	60.0	71.0	71.0	61.3	130.0	71.0
	Level (dB)	8.5	5.0	7.0	13.5	-6.0	9.0
	Type	Bell	Bell	Bell	Bell	Bell	Bell
	Q	3.8	2.4	2.5	5.0	2.8	2.5
	Bandwidth	0.379	0.597	0.573	0.288	0.513	0.573
PEQ2	Freq (Hz)	212	125	250	212	500	250
	Level (dB)	4.0	-3.0	-1.5	4.0	-1.5	-1.5
	Type	Bell	Bell	Bell	Bell	Bell	Bell
	Q	5.0	3.3	2.0	5.0	2.5	2.0
	Bandwidth	0.288	0.436	0.714	0.288	0.573	0.714
PEQ3	Freq (Hz)	410	500	1450	410	850	1450
	Level (dB)	2.0	-2.0	-3.0	2.0	-3.0	-3.0
	Type	Bell	Bell	Bell	Bell	Bell	Bell
	Q	5.0	2.0	4.2	5.0	5.0	4.2
	Bandwidth	0.288	0.714	0.343	0.288	0.288	0.343
PEQ4	Freq (Hz)	1,320	2,300	2,800	1,320	2,300	2,800
	Level (dB)	-1.0	-2.0	-2.0	-1.0	-2.0	-2.0
	Type	Bell	Bell	Bell	Bell	Bell	Bell
	Q	2.2	4.7	4.2	2.2	4.7	4.2
	Bandwidth	0.650	0.306	0.343	0.650	0.306	0.343
PEQ5	Freq (Hz)	4,750	3,750	4,500	4,750	3,550	4,500
	Level (dB)	-1.5	-3.0	-1.5	-2.0	-3.0	-1.5
	Type	Bell	Bell	Bell	Bell	Bell	Bell
	Q	1.3	4.7	4.5	1.3	4.2	4.5
	Bandwidth	1.084	0.306	0.320	1.084	0.343	0.320
PEQ6	Freq (Hz)	12,500	15,000	14,000	12,500	15,000	14,000
	Level (dB)	3.0	-7.0	-3.0	3.0	-6.50	-3.0
	Type	Bell	Bell	Bell	Bell	Bell	Bell
	Q	1.8	2.0	2.7	1.8	2.0	2.7
	Bandwidth	0.792	0.714	0.531	0.792	0.714	0.531
Limiter	Threshold	500W	500W	350W	500W	500W	350W
	Attack	MID	MID	MID	MID	MID	MID
	Release	MID	MID	MID	MID	MID	MID